



滑动摩擦副：钢 / PTFE 复合材料

Sliding contact surfaces: Steel / PTFE composite material

轴承 型号 Bearing number	外形尺寸 Dimensions																额定载荷 Load ratings		重量 Weight ≈kg
	mm																kN		
	d	B	d _K	C ₁ max	d ₂	G 6H	h ₁	l ₃ min	l ₄	l ₅	l ₇	W	d ₃	d ₄	r _s min	α° ≈	动载荷 Dynamic	静载荷 Static	
SIJK5C	5	8	11.112	7.5	18	M5	27	8	36	4	10	10	9	12	0.3	4	3.6	4.6	0.016
SIJK6C	6	9	12.7	7.5	20	M6	30	9	40	5	11	10	10	13	0.3	9	4.7	5.2	0.022
SIJK8C	8	12	15.88	9.5	24	M8	36	12	48	5	13	13	12.5	16	0.3	12	7.6	8.2	0.047
SIJK10C	10	14	19.05	11.5	30	M10	43	15	58	6.5	16	16	15	19	0.3	10	12	15	0.088
SIJK10C/B1						M10×1.25													
SIJK12C	12	16	22.23	12.5	34	M12	50	18	67	6.5	18	18	17.5	22	0.3	12	14	19	0.14
SIJK12C/B2						M12×1.25													
SIJK14C	14	19	25.4	14.5	38	M14	57	21	76	8	20	21	20	25	0.3	14	19	24	0.20
SIJK14C/B1						M14×1.5													
SIJK16C	16	21	28.58	15.5	42	M16	64	24	85	8	21	24	22	27	0.3	14	23	29	0.25
SIJK16C/B1						M16×1.5													
SIJK18C	18	23	31.75	17.5	46	M18×1.5	71	27	94	10	22.5	27	25	31	0.6	13	29	34	0.35
SIJK20C	20	25	34.93	18.5	50	M20×1.5	77	30	102	10	25	30	27.5	34	0.6	14	34	40	0.43
SIJK22C	22	28	38.1	21	56	M22×1.5	84	33	112	12	27.5	34	30	37	0.6	14	42	50	0.61
SIJK25C	25	31	42.86	23	60	M24×2	94	36	124	12	28.5	36	33.5	42	0.6	14	52	57	0.81
SIJK28C	28	35	47.63	26	66	M27×2	103	41	136	14	31.5	41	37	46	0.6	14	66	69	1.2
SIJK30C	30	37	50.8	27	70	M30×2	110	45	145	15	33	46	40	50	0.6	15	73	77	1.4

可提供不同螺距或螺纹精度有特殊要求的杆端关节轴承。Can supply other rod ends with different pitch or accuracy of thread.

若是左旋螺纹，轴承型号和螺纹标记需加“L”和“左”，例如：SIJK20C M20×1.5 左-6H。

For left-hand thread, suffix “L” is added to bearings number and thread sign, e.g. SIJK20C M20×1.5L-6H.

上列产品用不锈钢制造（杆端体和内圈），轴承型号后面加“X”标识，即 SIJK...C/X。

The rod and inner ring of the bearings is of stainless steel and the mark of the items has a letter “X”. That is SIJK...C/X.