



滑动摩擦副: 钢 / 青铜

Sliding contact surfaces: Steel / Bronze

轴承 型号 Bearing number	外形尺寸 Dimensions											额定载荷 Load ratings kN		重量 Weight ≈kg	
	d	B	dk	C ₁ max	d ₂	G 6g	h	l ₁ min	l ₂	l ₇	r _s min	α° ≈	动载荷 Dynamic		静载荷 Static
SABP5S	5	8	11.112	6	16	M5	33	20	41	—	0.3	13	3.3	3.9	0.016
SABP6S	6	9	12.7	6.75	18	M6	36	22	45	—	0.3	13	4.3	5.3	0.026
SABP8S	8	12	15.88	9	22	M8	42	25	53	—	0.3	14	6.8	8.5	0.044
SABP10S	10	14	19.05	10.5	26	M10	48	29	61	—	0.3	14	10	11	0.072
SABP12S	12	16	22.23	12	30	M12	54	33	69	—	0.3	13	13	14	0.108
SABP14S	14	19	25.4	13.5	34	M14	60	36	77	—	0.3	16	17	20	0.161
SABP16S	16	21	28.58	15	38	M16	66	40	85	—	0.3	15	21	25	0.225
SABP18S	18	23	31.75	16.5	42	M18×1.5	72	44	93	23	0.6	15	26	30	0.295
SABP20S	20	25	34.93	18	46	M20×1.5	78	47	101	25	0.6	15	31	35	0.382
SABP22S	22	28	38.1	20	50	M22×1.5	84	51	109	27	0.6	15	38	43	0.488
SABP25S	25	31	42.86	22	60	M24×2	94	57	124	29	0.6	15	47	65	0.749
SABP28S	28	35	47.63	25	66	M27×2	103	62	136	33	0.6	15	59	77	0.949
SABP30S	30	37	50.8	25	70	M30×2	110	66	145	39	0.6	17	63	86	1.13

可提供不同螺距或螺纹精度有特殊要求的杆端关节轴承。Can supply other rod ends with different pitch or accuracy of thread.

若是左旋螺纹, 轴承型号和螺纹标记需加“L”和“左”, 例如: SALBP20S M20×1.5 左-6g。

For left-hand thread, suffix “L” is added to bearings number and thread sign, e.g. SALBP20S M20×1.5L-6g.

上列产品用不锈钢制造 (杆端体和内圈), 轴承型号后面加“X”标识, 即 SABP...S/X。

The rod and inner ring of the bearings is of stainless steel and the mark of the items has a letter “X”. That is SABP...S/X.